



CTA Glazing Decals



CTA provides visual indicators for glazed doors to ensure building entrances meet NCC access requirements for the vision impaired.

Fully glazed doors represent a significant safety hazard to the vision impaired, who tend to focus only a short distance in front of themselves as they walk. This risk can be mitigated by the application of well designed, highly visible decals or visual indicators to these doors.

CTA provides well designed solutions so a person with vision impairment is able to detect the visual barrier.

CTA ensures the luminance contrast criteria, and the dimensional criteria of decal width and installation height have all been met.

KEY FEATURES

- UV resistant vinyl
 - Peel and stick install
 - A range of colours, designs and custom options
 - Meets all the requirements of AS1428 and AS1288
 - CTA will ensure the install meets all luminance contrast requirements
 - Fast turnaround time
 - Guaranteed installation
-

MATERIAL

UV resistant quality vinyl with 'peel and stick' install.

APPLICATIONS

Easy to install onto all fully glazed doors.

COLOUR

A range of colours is available, or custom-made decals can be ordered incorporating a design such as a company logo.

INSTALLATION

CTA can professionally install the decals to existing doors to ensure compliance with the standards and the BCA, or you can choose to have decals supplied only.

WARRANTY

CTA provides a comprehensive warranty, in accordance with our published warranty statement which can be viewed on cobbletac.com.

CTA INSTALLERS

CTA's accredited installers are available to do the installation work for you – with short turnaround times and guaranteed workmanship.

COMPLIANCE

The Building Code of Australia (BCA), through reference to AS1428.1 at D3.3(c) and AS1288, provides technical details of requirements for the location, dimensioning and luminance contrast of visual indicators. These criteria are:

- The visual indicators are located at the appropriate height above the finished floor, i.e. between 900 and 1000mm above the finished floor level
- The visual indicators are the full width of the door and sidelight
- The visual indicators are not be less than 75mm wide
- The visual indicator is solid and continuous. Note broken lines, symbols or words may not achieve the required effect.

CTA supplies decals which fully comply with AS1428.1 and AS1288, meeting luminance contrast, width and continuity requirements.

LUMINANCE CONTRAST

The luminance contrast of the indicators of at least 30% is achieved when viewed by a person with a depth of field limitation. The background in all cases will be the circulation space on the opposite side of the door.

CALL CTA ON 1300 282 282
TO ARRANGE A MEETING WITH A SALES CONSULTANT

VICTORIA 1300 282 282 NEW SOUTH WALES 1300 282 679 QUEENSLAND 1300 282 753 WA 1300 282 282



WWW.CTAGROUP.COM.AU