



# SafeLine® Tape



SafeLine® Tape provides easy Peel&Stick application of durable, P5 anti-slip rated safety tape onto almost any smooth surface. It is the proven option to ensure safety with minimal fuss.

SafeLine® Tape is manufactured from a unique combination of aluminium oxide and a thick plastic carrier to provide a flexible yet durable anti-slip solution. The carrier and adhesive is formulated to resist water, steam and detergent and will withstand temperatures below -30°C and up to 120°C continuously. The unique flexibility of SafeLine® will also allow extreme bending, even over 90° angles without damage.

SafeLine® is supplied with a Peel&Stick pressure sensitive adhesive (PSA) backing that ensures permanent adhesion to most smooth surfaces and is an efficient way of ensuring safety with minimal fuss.

## KEY FEATURES

- Easy to install with no fuss - ideal for DIY applications
- Provide an P5 safety rating, the highest in the industry
- Withstand temperatures below -30°C and up to 120°C
- Available in 7 colours including hazard, clear and luminescent
- Can be retro-fitted onto ceramic tiles, timber, metal and almost any other smooth surface
- Available in 25, 31, 50, 100, 150 and 200mm widths



## PRODUCT OPTIONS

WIDTH	LENGTH	PRODUCT CODE
25mm	18.3m	SNCT25-XXX
31mm	18.3m	SNCT31-XXX
50mm	18.3m	SNCT50-XXX
100mm	18.3m	SNCT100-XXX
150mm	18.3m	SNCT150-XXX
200mm	18.3m	SNCT200-XXX

Where XXX = tape colour (see right).

## MATERIAL

Manufactured from a unique combination of aluminium oxide and a thick plastic carrier to provide a flexible yet durable anti-slip solution.

## APPLICATIONS

SafeLine® Tape is suitable for:

- Internal flooring surfaces prone to water or oil spillage
- Stairs and pedestrian ramps
- Demarcating isles and walkways
- Expansion joint cover plates
- Marine pleasure craft
- Bathrooms and pool areas

## DIMENSIONS

SafeLine® Tape is available in 18.3m rolls, and widths of 25, 31, 50, 100, 150 and 200mm.

## INSTALLATION

Easy Peel&Stick install

## COLOURS



## COMPLIANCE

All CTA products conform with the requirements of the Australian standards and are tested by NATA certified labs.

Please consult with CTA for relevant test reports:

- AS1428:2009 Design for access and mobility
- AS4586:2013 Slip resistance classifications for new pedestrian surface materials
- NCC - National Construction Codes

## LUMINANCE CONTRAST

Please view the CTA Luminance Brochure for details or contact your CTA representative to discuss or request an onsite luminosity test.

## WARRANTY

CTA provides a comprehensive warranty, in accordance with our published warranty statement which can be viewed on [cobbletac.com](http://cobbletac.com).

## CTA COMPLETE CARE MAINTENANCE

Asset owners have a Duty of Care responsibility to maintain access product within design performance parameters. CTA offers a fully integrated maintenance program which includes regular scheduled maintenance and replacement of worn components where necessary. Please contact your CTA representative for information on our "Complete Care Program."

## CTA INSTALLERS

CTA's accredited installers are available to do the installation work for you – with short turnaround times and guaranteed workmanship. Our installation team is the largest and most experienced in the nation, so you can rest assured you are in safe hands.

## MORE INFORMATION

Product Installation, list of Approved Products and Material Safety Data Sheets are available on request.

**CALL CTA ON 1300 282 282**  
TO ARRANGE A MEETING WITH A SALES CONSULTANT

VICTORIA 1300 282 282 NEW SOUTH WALES 1300 282 679 QUEENSLAND 1300 282 753 WA 1300 282 282



[WWW.CTAGROUP.COM.AU](http://WWW.CTAGROUP.COM.AU)