



# GraniTac<sup>®</sup>



GraniTac<sup>®</sup> tactile indicator pavers, manufactured from natural granite, offer the outstanding durability of granite and combine this legendary durability with a wonderful natural appearance.

Architects and landscape designers will appreciate the breadth that GraniTac<sup>®</sup> adds to their tactile product choice. Project managers will appreciate a product which is easily incorporated without interrupting construction timelines. Building managers will appreciate a product that is permanent, needing little if any maintenance over many years.

And while GraniTac<sup>®</sup> tactile indicators are ideal for the most demanding external environments, they can also be used to complement modern internal designs.

Also available in GraniTac<sup>®</sup> Select.

## KEY FEATURES

- Available in both hazard (stud) and directional (rib) profiles
- Very high R12 slip resistance rating, exceeding AS4586 requirements in wet and dry conditions
- Meets AS1428 tactile design requirements
- Colour and size stable
- Standard installation using normal paving practices with 2-3mm grouting between the tiles
- Available with 20mm base, 40mm for GraniTac Select.



**PRODUCT OPTIONS**

COLOUR OPTION	SIZE	PRODUCT CODE HAZARD STUD	PRODUCT CODE DIRECTIONAL RIB
Ivory	300 x 300 x 20mm base	HGT108CT	DGT108CT
Yellow	300 x 300 x 20mm base	HGT112CT	DGT112CT
Grey	300 x 300 x 20mm base	HGT155CT	DGT155CT
Black	300 x 300 x 20mm base	HGT160CT	DGT160CT
Ivory over Blue Stone	300 x 300 x 40mm base	HGTS108CT	DGTS108CT
Blue Stone over Ivory	300 x 300 x 40mm base	HGTS135CT	DGTS135CT

Also available in 400 x 400mm on request

**MATERIAL**

Natural granite stone. GraniTac® tactile indicators have inherited the benefits of granite making them the most hard wearing and reliable tactile products on the market.

**APPLICATIONS**

GraniTac® tactile indicators are designed for permanent installation into pavements, paths and ramps. Ideally suited to challenging external applications, they can also be installed internally into concrete, tiled or paved floors.

**DIMENSIONS**

Standard 300mm x 300mm dimensions and 5mm stud height, GraniTac® has a 20mm base, 40mm for GraniTac® Select. Also available in 400mm x 400mm format on request.

**INSTALLATION METHOD**

GraniTac® Tactiles must be laid level with the surrounding surface so that the tactile stud stands proud. A recess (25mm or 45mm for GraniTac® and GraniTac® Select respectively) must be provided, the tactiles are laid into this recess using an approved adhesive applied with a suitable square notched trowel. GraniTac® Select being 40mm thick can be laid as a paver on a suitable base of sand/cement. Floor traffic should be avoided ideally for 48 hours or at least for 24 hours after installation. See Product Installation sheet for full instructions.


**PRODUCT DATA**

Dimensions (Standard)	300 x 300 x 20+5
Dimensions (Select)	300 x 300 x 40+5
Weight (Standard)	5.5 kg
Weight (Select)	9.5 kg
AS1428 Compliant	Yes
AS4586 - Wet Pendulum	77 / P5
AS4586 - Oil-Wet Ramp	R12
NCC Compliant	Yes
Materials	Natural Granite
UV Stable	Yes
Warranty	10 Years
Life Expectancy	25+ years
Indoor Use	If suitable
Outdoor Use	Yes

**COLOURS**



**INSTALLATION**



**COMPLIANCE**

All CTA products conform with the requirements of the Australian standards and are tested by NATA certified labs.

Please consult with CTA for relevant test reports:

- AS1428:2009 Design for access and mobility
- AS4586:2013 Slip resistance classifications for new pedestrian surface materials
- NCC - National Construction Codes

**LUMINANCE CONTRAST**

Please view the CTA Luminance Brochure for details or contact your CTA representative to discuss or request an onsite luminosity test.

**WARRANTY**

CTA provides a comprehensive warranty, in accordance with our published warranty statement which can be viewed on [cobbletac.com](http://cobbletac.com).

**CTA COMPLETE CARE MAINTENANCE**

Asset owners have a Duty of Care responsibility to maintain access product within design performance parameters. CTA offers a fully integrated maintenance program which includes regular scheduled maintenance and replacement of worn components where necessary. Please contact your CTA representative for information on our "Complete Care Program."

**CTA INSTALLERS**

CTA's accredited installers are available to do the installation work for you – with short turnaround times and guaranteed workmanship. Our installation team is the largest and most experienced in the nation, so you can rest assured you are in safe hands.

**MORE INFORMATION**

Product Installation, list of Approved Products and Material Safety Data Sheets are available on request.

**CALL CTA ON 1300 282 282**  
**TO ARRANGE A MEETING WITH A SALES CONSULTANT**

VICTORIA 1300 282 282 NEW SOUTH WALES 1300 282 679 QUEENSLAND 1300 282 753 WA 1300 282 282



[WWW.CTAGROUP.COM.AU](http://WWW.CTAGROUP.COM.AU)