



PolyCap®



CTA PolyCap® combines the aesthetic qualities of the SureSteel® range with the versatility and colour options of the extremely popular PolyStud® range of tactiles.

Manufactured from a UV stable polymer with a brushed stainless steel cap, PolyCap® offers architects and designers greater flexibility when choosing tactiles.

When the superb one-piece stainless steel design of the SureSteel® Select range can't be justified, PolyCap® is the perfect product to achieve the same aesthetic and range of colours at a reduced cost.

Based on the proven design of the PolyStud® range, PolyCap® is engineered and purpose built tough to withstand heavy impact and be long lasting.

KEY FEATURES

- R11 safety rating
- Low maintenance and long lasting
- Easy, no adhesive install, and indicators can be walked on immediately
- Excellent aesthetic
- Meet the requirements of AS1428 - Design for Access and Mobility
- Installation templates can be provided for simple do-it-yourself installation



PRODUCT OPTIONS

COLOUR OPTION	PRODUCT CODE
Ivory	TSPC-108
Yellow	TSPC-112
Terracotta	TSPC-124
Ocean Blue	TSPC-135
Grey	TSPC-155
Black	TSPC-160

MATERIAL

Manufactured from new generation polymers and stainless cap. Designed to provide optimum durability, UV stability and wear resistance.

APPLICATIONS

PolyCap® indicators can be installed over almost any substrate, including concrete, bitumen, natural stone, ceramic tiles, pavers, timber, carpet and most other surfaces. Individual discrete tactile indicators are designed to expose the underlying substrate, and provide many design options. Suitable for internal and external applications.

DIMENSIONS

A major diameter of 35mm, and a minor diameter of 25mm, with a protrusion height of 5mm, the maximum to ensure longevity and optimum anti-slip. 8mm x 20mm retention fit spigot.

INSTALLATION METHOD

PolyCap® Tactile indicators are installed into holes in the substrate pre-drilled with a suitable masonry or diamond tipped wet core drill bit. PolyCap® tactiles are designed with a retention fit spigot and do not require adhesive. Due the weakness of bituman, it is suggested that polyurethane adhesive is injected into each hole to provide greater substrate stability and further secure the tactile spigot. When installing over carpet/underlay, a pre-drilled filler board is required as a replacement to the underlay.




PRODUCT DATA

Product Weight	7g
Quantity in Package	100, 500 & 1000
Package Weight	0.7kg, 3.5kg & 7kg
AS1428 Compliant	Yes
AS4586 - Wet Pendulum	72 / P5
AS4586 - Oil-Wet Ramp	23.2° / R11
NCC Compliant	Yes
Materials	Polymer with Stainless cap
UV Stable	Yes
Warranty	2 Years
Life Expectancy	10+ years
Indoor Use	Yes
Outdoor Use	Yes

COLOURS



INSTALLATION



COMPLIANCE

All CTA products conform with the requirements of the Australian standards and are tested by NATA certified labs.

Please consult with CTA for relevant test reports:

- AS1428:2009 Design for access and mobility
- AS4586:2013 Slip resistance classifications for new pedestrian surface materials
- NCC - National Construction Codes

LUMINANCE CONTRAST

Please view the CTA Luminance Brochure for details or contact your CTA representative to discuss or request an onsite luminosity test.

WARRANTY

CTA provides a comprehensive warranty, in accordance with our published warranty statement which can be viewed on cobbletac.com.

CTA COMPLETE CARE MAINTENANCE

Asset owners have a Duty of Care responsibility to maintain access product within design performance parameters. CTA offers a fully integrated maintenance program which includes regular scheduled maintenance and replacement of worn components where necessary. Please contact your CTA representative for information on our "Complete Care Program."

CTA INSTALLERS

CTA's accredited installers are available to do the installation work for you - with short turnaround times and guaranteed workmanship. Our installation team is the largest and most experienced in the nation, so you can rest assured you are in safe hands.

MORE INFORMATION

Product Installation, list of Approved Products and Material Safety Data Sheets are available on request.

CALL CTA ON 1300 282 282
TO ARRANGE A MEETING WITH A SALES CONSULTANT

VICTORIA 1300 282 282 NEW SOUTH WALES 1300 282 679 QUEENSLAND 1300 282 753 WA 1300 282 282



WWW.CTAGROUP.COM.AU